

Bijlage bij het BENOR productcertificaat nr. 282/2322/0322 uitgereikt op 1.01.2026.

Productie-eenheid:

THE SIAM INDUSTRIAL WIRE Co. Ltd
 555 Rasa One (Building A) - 14th Floor
 Phaholyothin Road
 TH-10900 BANGKOK

Telefoon: +66/ 937 0060

Fax: +66/ 937 0068

E-mail: Sunanta_t@siw.co.th

Producten:

Voorspanstaal			Karakteristieken van de erkende producten			
Familie	Treksterkte N/mm ²	Type	Diameters	Relaxatie klasse	Vervaardiging	Afbuigtrekproef
3	1670	Gedeukte draad	7	R2	S	/
		Gladde draad	7	R2	S	/
4	1770	Gedeukte draad	4 - 5 - 6 - 7	R2	S	/
		Gladde draad	4 - 5 - 6 - 7	R2	S	/
4 bis	1860	Gedeukte draad	4 - 5	R2	S	/
		Gladde draad	4 - 5	R2	S	/
6	1860	3-draadsstreng	-	-	-	-
		7-draadsstreng	9,3 12,5 - 12,9 15,2 - 15,7	R2	S	D ≤ 20 (diam ≥ 12 mm)
		3-draadsstreng gedeukt	-	-	-	-
		7-draadsstreng gedeukt	-	-	-	-
7	1920	3-draadsstreng	-	-	-	-
9	2060	3-draadsstreng	-	-	-	-
		7-draadsstreng	-	-	-	-
P	1860	Beschermde omhulde 7-draadstreng	15,2 - 15,7	R2	S	D ≤ 20

Verkoopkantoor:

THE SIAM INDUSTRIAL WIRE Co. Ltd, 555 Rasa
 One (Building A) - 14th Floor Phaholyothin
 Road, TH-10900 BANGKOK

Annexe au certificat produit BENOR no. 282/2322/0322 délivré le 1.01.2026.
Unité de production:

THE SIAM INDUSTRIAL WIRE Co. Ltd
 555 Rasa One (Building A) - 14th Floor
 Phaholyothin Road
 TH-10900 BANGKOK

Téléphone: +66/ 937 0060

Fax: +66/ 937 0068

E-mail: Sunanta_t@siw.co.th

Produits:

Acier précontraint			Caractéristiques de produits agréés			
Famille	Résistance à la traction N/mm ²	Type	Diamètre	Relaxation classe	Fabrication	Traction déviée
3	1670	Fils à empreinte	7	R2	S	/
		Fils lisse	7	R2	S	/
4	1770	Fils à empreinte	4 - 5 - 6 - 7	R2	S	/
		Fils lisse	4 - 5 - 6 - 7	R2	S	/
4 bis	1860	Fils à empreinte	4 - 5	R2	S	/
		Fils lisse	4 - 5	R2	S	/
6	1860	Torons 3 fils	-	-	-	-
		Torons 7 fils	9,3 12,5 - 12,9 15,2 - 15,7	R2	S	D ≤ 20 (diam ≥ 12 mm)
		Torons à empreintes 3 fils	-	-	-	-
		Torons à empreintes 7 fils	-	-	-	-
7	1920	Torons 3 fils	-	-	-	-
9	2060	Torons 3 fils	-	-	-	-
		Torons 7 fils	-	-	-	-
P	1860	Torons protégés gainés 7 fils	15,2 - 15,7	R2	S	D ≤ 20

Organisme de vente:

THE SIAM INDUSTRIAL WIRE Co. Ltd, 555 Rasa One (Building A) - 14th Floor Phaholyothin Road, TH-10900 BANGKOK

Annex to the BENOR product certificate nr. 282/2322/0322 delivered on 1.01.2026.

Production unit:

THE SIAM INDUSTRIAL WIRE Co. Ltd
 555 Rasa One (Building A) - 14th Floor
 Phaholyothin Road
 TH-10900 BANGKOK

Phone: +66/ 937 0060

Fax: +66/ 937 0068

E-mail: Sunanta_t@siw.co.th

Products:

Prestressing steel			Characteristics of the approved products			
Family	Tensile strength N/mm ²	Type	Diameter	Relaxation class	Production	Deviated tensile test
3	1670	Indented wires	7	R2	S	/
		Smooth wires	7	R2	S	/
4	1770	Indented wires	4 - 5 - 6 - 7	R2	S	/
		Smooth wires	4 - 5 - 6 - 7	R2	S	/
4 bis	1860	Indented wires	4 - 5	R2	S	/
		Smooth wires	4 - 5	R2	S	/
6	1860	3-wire strands	-	-	-	-
		7-wire strands	9,3 12,5 - 12,9 15,2 - 15,7	R2	S	D ≤ 20 (diam ≥ 12 mm)
		Indented 3-wire strands	-	-	-	-
		Indented 7-wire strands	-	-	-	-
7	1920	3-wire strands	-	-	-	-
9	2060	3-wire strands	-	-	-	-
		7-wire strands	-	-	-	-
P	1860	Protected and sheathed 7-wire strands	15,2 - 15,7	R2	S	D ≤ 20

Sales office:

THE SIAM INDUSTRIAL WIRE Co. Ltd, 555 Rasa
 One (Building A) - 14th Floor Phaholyothin
 Road, TH-10900 BANGKOK